



1st WHEN IT COMES TO YOUR 2nd

1. Picatinny Base
2. Miok Base
3. Locking Radius
4. Barricade Stop/Grip
5. Locking Lug
6. Locking Knob
7. Kydes Locking Block



M-LOK Base
 You will receive the mount configured in the M-LOK setup. The locking radius will be secured using two 6/32 x 3/8 bolts along with two 6/32 nuts. To access the M-LOK bolts, start by removing the barricade stop/grip. Position the mount at the desired position on the rail, then securely tighten the M-LOK bolts.

Afterward, reattach the barricade stop/grip at the preferred angle. Next, connect the locking lug on the opposite side, directly across from the barricade stop/grip, and push the two components together to lock them into place. Finally, secure the barricade stop/grip by tightening the knob. The mount is now ready for use.

Picatinny Base
 When using the Picatinny base, begin by removing the locking radius from the M-LOK base. Secure it to the Picatinny base using the two 6/32 x 1/2 inch bolts and the two 6/32 nuts. Tighten the bolts until the tips are flush with the nuts, allowing the mount to slide freely along the rail.

Next, locate the desired position on the rail for securing the mount. The Kydex locking block should be placed in the valley of the Picatinny rail, directly beneath the two 6/32 bolts. Slowly tighten the bolts, ensuring contact is made with the Kydex locking block rather than the rail. Alternate tightening each bolt gradually to avoid over-tightening.

Once the mount is secured in place, slide the barricade stop/grip to the desired angle. Connect the locking lug on the opposite side, directly across from the barricade stop/grip, and push the two parts together to lock them into place using the locking knob. Finally, secure the barricade stop/grip by tightening the knob. Your mount is now ready for use.

The mount is designed for easy adjustment to accommodate individual comfort and ergonomics, allowing for quick relocation if necessary. Constructed from reinforced polymer, the Cicada Tactical mount is a lightweight, rugged, and modular accessory.

- (Utilized with the Picatinny Base)
8. Stainless Steel Hardware Included
 - a. (2) 6/32x1/2" Bolts (Picatinny Base)
 - b. (2) 6/32x3/8" Bolts (Miok Base)
 - c. (2) 6/32 Nuts for Locking Radius
 - d. MS Bolt for Locking Lug




The grip is adjustable from 0° to 75° to the left or right in 15° increments. It can be positioned in the 3, 6, 9, or 12 o'clock locations on the weapon's Picatinny or M-LOK systems.

The mount is designed for enhanced ergonomics, enabling shooters to position the vertical grip in an optimal location that best suits their comfort. This improvement in comfort significantly reduces operator fatigue, leading to prolonged mission capabilities. This mount has also been shown to facilitate quicker target acquisition, enhancing shot accuracy and increasing the speed of the cyclic rate of fire.



Barricade Stop/Grip



Locking Lug



Locking Knob



Vertical



Rotated at 30°



Locking Radius



M-LOK Base



Picatinny Base